



Model

R700

GIGABIT

Multi-WAN VPN Router



Datasheet



Features

- Gigabit Ethernet Ports
- Up to 4 WAN Ports
- PPTP/L2TP/OpenVPN/WireGuard/IPsec VPN
- Link Backup and Load Balance

Specifications

Product Description	Gigabit Multi-WAN VPN Router
Product Model	R700
Standards and Protocols	IEEE 802.3, IEEE802.3u, IEEE802.3ab, IEEE 802.3x TCP/IP, DHCP, ICMP, NAT, PPPoE, HTTP, DNS, IPSec, PPTP, L2TP, OpenVPN, WireGuard, Zerotier
Interface	1 Gigabit WAN port 3 Gigabit LAN/WAN ports 1 Gigabit LAN ports
Network Media	10BASE-T: UTP category 3, 4, 5 cable (Max 100 m) EIA/TIA-568 100Ω STP (Max 100 m) 100BASE-TX: UTP category 5, 5e cable (Max 100 m) EIA/TIA-568 100Ω STP (Max 100 m) 1000BASE-T: UTP category 5e, 6 cable (Max 100 m)
Button	Reset Button
Power Supply	External 12V/1A DC Adapter
Flash	16 MB NOR Flash
DRAM	128 MB DDR
LED	PWR, SYS, WAN (Link/Act), LAN (Link/Act)
Dimensions (W x D x H)	119×85×28 mm



Concurrent Session	15,360
New Sessions /Second	2,600
WAN Connection Type	Static IP Dynamic IP PPPoE
DHCP	DHCP Server DHCP Address Reservation
MAC Clone	Modify WAN/LAN MAC Address
IPv6	Relay Dynamic(SLAAC/DHCPv6) Static (Fixed IP) Passthrough MAP-E (Dual-stack) DS-Lite (Dual-stack)
Load Balance	Intelligent Load Balance Link Backup (Timing, Failover) Online Detection
NAT	Virtual Server Port Triggering NAT-DMZ FTP/H.323/SIP/IPSec/PPTP ALG, UPnP

Routing	Static Routing Policy Routing
IPSec VPN	Main, Aggressive Negotiation Mode 3DES, AES128, AES192, AES256 Encryption Algorithm IKE v1/v2, MD5, SHA1, SHA2,SHA254,SHA386, SHA512 Authentication Algorithm, Dead Peer Detection (DPD)
PPTP VPN	PPTP VPN Server PPTP VPN Client PPTP with MPPE Encryption
L2TP VPN	L2TP VPN Server L2TP VPN Client L2TP Over IPSec
OpenVPN	OpenVPN Server OpenVPN Client
Firewall	SPI DoS Block Ping from WAN
Filtering	MAC Filtering Domain Filtering IP Filtering



Maintenance	Web Management Interface
	Remote Management
	Export & Import Configuration
	Diagnostics (Ping & Traceroute&NSLookup)
	Syslog Support
Certification	CE, FCC, RoHS
Package Contents	R700, Power Adapter, RJ-45 Ethernet Cable, Quick Installation Guide
System Requirements	Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7/8/8.1/10 MAC OS, NetWare, UNIX or Linux
Environment	Operating Temperature: 0 °C to 40 °C (32 °F to 104 °F) Storage Temperature: -40 °C to 70 °C (-40 °F to 158 °F) Operating Humidity: 10% to 90% non-condensing Storage Humidity: 5% to 90% non-condensing